



SCM0002 – Methane emission reduction by adjusted water management practice in rice cultivation

Document Prepared by the Social Carbon Foundation

Title	Methane emission reduction by adjusted water management practice in rice cultivation
Version	V1.0

Date of Issue	29/04/2022
Type	Methodology
Sectoral Scope	Scope 15 – Agriculture
Prepared By	Social Carbon Foundation
Contact	Kemp House, 160 City Road, London, United Kingdom, EC1V 2NX

Contents

Methodology Details	3
1. Sources	3
2. Summary description of the Methodology	3
3. Definitions.....	4
4. Applicability Conditions.....	6
5. Project Boundary	7
6. Baseline Scenario	7
7. Additionality	7
8. Quantification of GHG Emission Reductions	8
9. Monitoring.....	14
10. References	19
Appendix 1: Guidelines for measuring methane emissions from rice fields.....	20

Methodology Details

1. Sources

This methodology revision applies to CDM small-scale methodology AMS-III.AU, “Methane emission reduction by adjusted water management practice in rice cultivation”. Project proponents must apply this methodology revision in conjunction with the latest version of AMS III.AU.

The methodology uses the following sources:

- SOCIALCARBON Standard Definitions
- CDM Tool for the demonstration and assessment of additionality version 5.2
- AMS-III.AU, “Methane emission reduction by adjusted water management practice in rice cultivation”.
- CDM General guidelines for SSC CDM methodologies, “Guidelines on the demonstration of additionality of small-scale project activities” and “General guidance on leakage in biomass project activities”

2. Summary description of the Methodology

The methodology comprises technology/measures that result in reduced anaerobic decomposition of organic matter in rice cropping soils and thus reduced generation of methane. The methodology includes projects such as:

- Rice farms that change the water regime during the cultivation period from continuously to intermittent flooded conditions and/or a shortened period of flooded conditions;
- Alternate wetting and drying method and aerobic rice cultivation methods¹;
- Rice farms that change their rice cultivation practice from transplanted to direct seeded rice.²

Additionality and Crediting Method	
Additionality	Project Method
Crediting Baseline	Project Method

The methodology is focused on GHG emission avoidance, through reduced anaerobic decomposition of organic matter in rice cropping soils.

The primary deviation to AMS-III.AU is that this methodology supports both small and large scale projects, that can generate more than 60,000 tCO₂e annually. In addition, monitoring can be conducted through remote sensing, provided the technology used has been peer-reviewed and has a known uncertainty.

¹ Saving water with alternative wetting drying (AWD). [Source](#)

² A switch from transplanted rice with continuously flooded fields to DSR leads to a reduced flooding period since DSR requires non-flooded conditions after sowing until the seed has fully germinated and developed into a viable, young plantlet (at the “2 to 4 leaf stage”).

3. Definitions

In addition to the definitions set out in the latest version of the SOCIALCARBON Standard Definitions, the following definitions apply to this methodology revision:

Transplanted rice

A system of planting rice where seeds are raised in a nursery bed for some 20 to 30 days. The young seedlings are then directly transplanted into the flooded rice field;

Direct seeded rice (DSR)

A system of cultivating rice in which seeds, either pre-germinated or dry, are broadcast or sown directly in the field under dry- or wetland condition; no transplanting process is involved;

IPCC approach

The most recent version of the applicable IPCC guidance on methane emission from rice cultivation. The applicable version at the time of approval of the methodology is chapter 5.5, volume 4 of the 2006 IPCC Guidelines for National Greenhouse Gas Inventories;

Project cultivation practice

A set of elements of a cultivation practice which is adopted under the CDM project activity. This mainly consists of the adjusted irrigation method. Field preparation, fertilization and weed and pest control may also be included;

Water regime

A combination of rice ecosystem type (e.g. irrigated, rainfed and deep water) and flooding pattern (e.g. continuously flooded, intermittently flooded);

Upland

A type of water regime in which fields are never flooded for a significant period of time;

Irrigated

A type of water regime in which fields are flooded for a significant period of time and water regime is fully controlled;

Rainfed and deep water

A type of water regime in which fields are flooded for a significant period of time and water regime depends solely on precipitation.

For the purpose of defining reference field conditions for baseline and project emission measurements and their comparison with project fields, classify each project field with its specific pattern of cultivation conditions, applying the following parameters under Table 2:

Table 2: Parameters for the definition of cultivation patterns

No.	Parameter	Type ^a	Values/categories	Source/Method ^b
1	Water regime – on-season ^c	Dynamic	Continuously flooded Single Drainage Multiple Drainage	Baseline: Farmer's information / Remote sensing Project: Monitoring
2	Water regime – pre-season	Dynamic	Flooded Short drainage (<180d) Long drainage (>180d)	Baseline: Farmer's information / Remote sensing Project: Monitoring
3	Organic Amendment	Dynamic	Straw on-season ^d Green manure Straw off-season ^e Farmyard manure Compost No organic amendment	Baseline: Farmer's information / Remote sensing Project: Monitoring
4	Soil pH	Static	<4.5 4.5 – 5.5 >5.5	ISRIC-WISE soil property database ^e or national data
5	Soil Organic Carbon	Static	<1% 1 – 3% >3%	ISRIC-WISE soil property database ^e or national data
6	Climate	Static	AEZ ^f	Rice Almanac, HarvestChoice ^f

Comments:

- (a) Dynamic conditions are those that are connected to the management practice of a field, thus can change over time (no matter whether intended by the project activity or due to other reasons) and shall be monitored in the project fields. Static conditions are site-specific parameters that characterize a soil and do not (relevantly) change over time and thus do in principle only have to be determined once for a project and the corresponding fields;
- (b) Source/method of data acquisition to determine the applicable value for each parameter;
- (c) The values 'upland', 'regular rainfed', 'drought prone' and 'deep water', which are regularly used to differentiate the on-season water regime (see IPCC guidelines), are not mentioned here, because these categories are excluded from a project activity under this methodology (cf. applicability criteria);
- (d) Straw on-season means straw applied just before rice season, and straw off-season means straw applied in the previous season. Rice straw that was left on the surface and incorporated into soil just before the rice season is classified as straw on-season;
- (e) For these static parameters, refer to appropriate global or national data. The database from ISRIC provides soil data which can be used for this purpose;

- (f) Climate zone: use agroecological zones as shown in the Rice Almanac (Third Edition, 2002), or by HarvestChoice.

With the help of this field characterization, project fields can be grouped according to their cultivation pattern. All fields with the same cultivation pattern form one group.

4. Applicability Conditions

This methodology is applicable under the following conditions:

- a) Rice cultivation in the project area is predominantly characterized by irrigated, flooded fields for an extended period of time during the growing season, i.e. farms whose water regimes can be classified as *upland* or *rainfed and deep water* are not eligible to apply this methodology. This shall be shown from a representative survey conducted in the geographical region of the proposed project or by using national data. This project area characterization shall also include information on pre-season water regime and applied organic amendments, so that all dynamic parameters as shown in Table 2 are covered by the baseline study;
- b) The project rice fields are equipped with controlled irrigation and drainage facilities such that both during dry and wet season, appropriate dry/flooded conditions can be established on the fields;
- c) The project activity does not lead to a decrease in rice yield. Likewise, it does not require the farm to switch to a cultivar that has not been grown before;
- d) Training and technical support during the cropping season that delivers appropriate knowledge in field preparation, irrigation, drainage and use of fertilizer to the farmer is part of the project activity and is to be documented in a verifiable manner (e.g. protocol of trainings, documentation of on-site visits). In particular the project proponent is able to ensure that the farmer by himself or through experienced assistance is able to determine the crop's supplemental N fertilization need. The applied method shall assess the fertiliser needs using for example a leaf colour chart or photo sensor or testing stripes. Alternatively, a procedure to ensure efficient fertilization considering the specific cultivation conditions in the project area backed by scientific literature or official recommendations shall be used;
- e) Project proponents shall assure that the introduced cultivation practice, including the specific cultivation elements, technologies and use of crop protection products, is not subject to any local regulatory restrictions;
- f) Except the case where the default value approach indicated in section 6.1.2 "Emission reductions using IPCC tier 1 approach or default values" is chosen for emission reductions calculations, project proponents have access to infrastructure to measure CH₄ emissions from reference fields using closed chamber method and laboratory analysis;

5. Project Boundary

The geographic boundary encompasses the rice fields where the cultivation method and water regime are changed. The spatial extent of the project boundary includes all fields that change the cultivation method in the context of the project activity.

Table 3 below identifies the GHG sources included or excluded from the project boundary.

Table 3: GHG Sources included in or excluded from the Project Boundary

Source	Gas	Included?	Explanation	
Baseline	Emissions from Rice cultivation	CO ₂	No	Negligible under applicability conditions
		CH ₄	Yes	Major pool considered in the baseline scenario
		N ₂ O	No	Negligible under applicability conditions
Project	Emissions from Rice cultivation	CO ₂	No	Negligible under applicability conditions
		CH ₄	Yes	Major pool considered in the project scenario
		N ₂ O	No	Negligible under applicability conditions

6. Baseline Scenario

The baseline scenario is the continuation of the current practice e.g. transplanted and continuously flooded rice cultivation in the project fields.

7. Additionality

This methodology uses a project method for the demonstration of additionality.

Step 1: Regulatory Surplus

Project proponents must demonstrate regulatory surplus in accordance with the rules and requirements regarding regulatory surplus set out in the latest version of the SOCIALCARBON Methodology Requirements.

Step 2: Project Method

The project activity shall apply the additionality analysis method set out in the latest version of the *CDM Tool for the Demonstration and Assessment of Additionality* to determine that the proposed project activity is either:

- 1) not the most economically or financially attractive; or
- 2) not economically or financially feasible; or
- 3) not common practice.

8. Quantification of GHG Emission Reductions

8.1 Baseline Reductions

The baseline emissions shall be calculated on a seasonal basis using the following formula:

$$BE_y = \sum_s BE_s \quad \text{(Equation 1)}$$

$$BE_s = \sum_{g=1}^G EF_{BL,s,g} \times A_{s,g} \times 10^{-3} \times GWP_{CH_4} \quad \text{(Equation 2)}$$

Where:

BE_y	=	Baseline emissions in year y ; tCO ₂ e
BE_s	=	Baseline emissions from project fields in season s ; tCO ₂ e
$EF_{BL,s,g}$	=	Baseline emissions factor of group g in season s ; kgCH ₄ /ha per season
$A_{s,g}$	=	Area of project fields of group g in season s ; ha
GWP_{CH_4}	=	Global Warming Potential of CH ₄ ; tCO ₂ e/tCH ₄
g	=	Group g , covers all project fields with the same cultivation pattern as determined with the help of Table 2 (G = total number of groups)

Determination of baseline emission factor on reference fields

Baseline reference fields shall be set up in a way that they are representative of baseline emissions in the project rice fields. For each group of fields with the same cultivation pattern, as defined with the help of Table 2, at least three reference fields with the same pattern shall be determined in the project area. On these fields, measurements using the closed chamber method shall be carried out, each resulting in an emission factor expressed as kgCH₄/ha per season. The seasonally integrated baseline emission factor $EF_{BL,s,g}$ shall be derived as average value from the three measurements for each group (see the appendix for guidelines on methane measurement)

8.2 Project Removals

Project emissions consist of the CH₄ emissions, which will still be emitted under the changed cultivation practice. Due to the optimized N fertilization practice, N₂O emissions do not significantly deviate from the baseline emissions and hence are not considered.

CH₄ emissions from project fields are calculated on a seasonal basis as follows:

$$PE_y = \sum_s PE_s \quad (\text{Equation 3})$$

$$PE_s = \sum_{g=1}^G EF_{P,s,g} \times A_{s,g} \times 10^{-3} \times GWP_{CH_4} \quad (\text{Equation 4})$$

Where:

PE_y = Project emissions in year y ; tCO₂e

PE_s = Project emissions from project fields in season s ; tCO₂e

$EF_{P,s,g}$ = Project emissions factor of group g in season s ; kgCH₄/ha per season

Determination of project emission factor on reference fields

The seasonally integrated project emission factor $EF_{P,s,g}$ shall be determined using measurements on at least three project reference fields that fulfil the same conditions as the baseline reference fields, with the difference that they are cultivated according to the defined project cultivation practice. Project reference fields shall be established close to the baseline reference fields and begin with the growing season at the same time. $EF_{P,s,g}$ is the average of the measurement results from the three reference fields.

8.3 Leakage

Any effects of the project activity on GHG emissions outside the project boundary are deemed to be negligible and do not have to be considered under this methodology.

8.4 Net GHG Emission Removals

The emission reductions achieved by the project activity shall be calculated as the difference between the baseline and the project emissions.

$$NER_y = BE_y - PE_y \quad (\text{Equation 5})$$

Where:

NER_y = Net emission reductions during year y ; tCO₂e

Ex ante estimation of emission reductions

For the ex ante estimation of emission reductions within the project design document (PDD), project participants shall either refer to own field experiments or estimate baseline and project emissions with the help of national data or IPCC tier 1 default values for emission and scaling factors. The approach shall be explained and justified in the PDD.

Emission reductions using IPCC tier 1 approach or default values

As an alternative to the reference field approach, project participants may calculate emission reductions using one of the following two simplified approaches (i.e. **Option 1** or **Option 2**):

Option 1: Using the IPCC tier 1 approach but undertaking measurements to determine baseline emission factors for continuously flooded fields, as per the following formula:

$$ER_y = EF_{ER} \times A_y \times L_y \times 10^{-3} \times GWP_{CH4} \quad (\text{Equation 6})$$

$$ER_{ER} = EF_{BL} - EF_p \quad (\text{Equation 7})$$

$$EF_{BL} = EF_{BL,c} \times SF_{BL,w} \times SF_{BL,p} \times SF_{BL,o} \quad (\text{Equation 8})$$

$$EF_p = EF_{BL,c} \times SF_{p,w} \times SF_{p,p} \times SF_{p,o} \quad (\text{Equation 9})$$

Where:

- ER_y = Emission reductions during year y ; tCO₂e
- EF_{ER} = Adjusted daily emission factor; kgCH₄/ha/day. Alternatively, seasonal emission factor (kgCH₄/ha/season) may be determined³
- A_y = Area of project fields in year y ; ha
- L_y = Cultivation period of rice in year y ; days/year. This is not applicable when seasonal emission factor is determined
- GWP_{CH4} = Global warming potential of CH₄; tCO₂e/tCH₄
- EF_{BL} = Baseline emission factor; kgCH₄/ha/day or kgCH₄/ha/season
- EF_p = Project emission factor; kgCH₄/ha/day or kgCH₄/ha/season
- $EF_{BL,c}$ = Baseline emission factor for continuously flooded fields without organic amendments; kgCH₄/ha/day or kgCH₄/ha/season
- $SF_{BL,w}$ or $SF_{p,w}$ = Baseline or project scaling factors⁴ to account for the differences in water regime during the cultivation period
- $SF_{BL,p}$ or $SF_{p,p}$ = Baseline or project scaling factors to account for the differences in water regime in the pre-season before the cultivation period
- $SF_{BL,o}$ or $SF_{p,o}$ = Baseline or project scaling factors should vary for both type and amount of organic amendment applied

The baseline emission factor for continuously flooded fields without organic amendments ($EF_{BL,c}$) shall be either determined ex ante prior to the start of the project activity (in this case the ex ante value should be used to calculate emission reduction during the crediting period) or monitored annually (in this case, the ex post values should be used to calculate emissions reduction during the crediting period). At least three reference fields shall be chosen in the project area. On these fields, measurements shall be carried out using the closed chamber method in accordance with the guidance on methane measurement in the appendix.

Alternatively, the baseline emission factor for continuously flooded fields with organic amendments may be determined. In this case, scaling factors to account for organic amendments ($SF_{BL,o}$ or $SF_{P,o}$) shall not be applied in the equations (8) and (9) above.

Table 3: IPCC default values for $SF_{BL,w}$ or $SF_{P,w}$

Water regime during the cultivation period		$SF_{BL,w}$ Or $SF_{P,w}$
Irrigated	Continuously flooded	1
	Intermittently flooded – single aeration	0.60
	Intermittently flooded – multiple aeration	0.52

Source: IPCC 2006, volume 4, chapter 5.5, Table 5.12

1. Continuously flooded: Fields have standing water throughout the rice growing season and may only dry out for harvest (end-season drainage).
2. Intermittently flooded: fields have at least one aeration period of more than three days during the cropping season;
 - a. Single aeration: fields have a single aeration during the cropping season at any growth stage (except for end-season drainage);
 - b. Multiple aeration: fields have more than one aeration period during the cropping season (except for end-season drainage).

³ In this methodology, “season” means an entire cropping season (from land preparation until harvest or post season drainage). If a seasonal emission factor is opted, it should be based on measurements over the entire period of flooding, and should account for fluxes of soil-entrapped methane that typically occur upon drainage.

⁴ For all scaling factors used in the methodology, the average values in 2006 IPCC Guidelines for National Greenhouse Gas Inventories are chosen. Uncertainties related to scaling factors may be considered in the future revision of the methodology.

IPCC default for $SF_{BL,p}$ or $SF_{P,p}$ is provided in the following table. For regions/countries where it can be demonstrated by official government data or peer-reviewed literature that double cropping is practiced, a default value of 1.0 is used. Otherwise, 0.68 is used.

Table 4: IPCC default values for $SF_{BL,p}$ or $SF_{P,p}$

Water regime prior to cultivation period	$SF_{BL,p}$ or $SF_{P,p}$
Non flooded pre-season < 180 days (indicating double cropping)	1
Non flooded pre-season < 180 days (indicating single cropping)	0.68

Source: IPCC 2006, volume 4, chapter 5.5, Table 5.12

IPCC default for $SF_{BL,o}$ or $SF_{P,o}$ is calculated as follows:

$$SF_o = \left(1 + \sum_i ROA_i \times CFOA_i\right)^{0.59} \quad \text{(Equation 10)}$$

Where:

- ROA_i = Application rate of organic amendment type i , in dry weight for straw and fresh weight for others, tonne ha⁻¹.
 5 tonne/ha of straw is assumed as the baseline quantity of organic amendment, because the value of leftover straw after harvest is in the range of 3 tonne/ha (when harvested manually to the ground level, leaving very little stubble and the root residues) to 7 tonne/ha (harvested mechanically leaving behind large amount of crop residues on the field)
- $CFOA_i$ = Conversion factor for organic amendment type i (in terms of its relative effect with respect to straw applied shortly before cultivation).
 0.29 is used for a single crop and 1.0 for a double crop⁵

Accordingly, default for $SF_{BL,o}$ or $SF_{P,o}$ is provided in the following table.

Table 5: IPCC default values for $SF_{BL,o}$ or $SF_{P,o}$

Water regime prior to cultivation period	$SF_{BL,o}$ or $SF_{P,o}$	
Non flooded pre-season < 180 days (indicating double cropping)	2.88	$SF_{BL,o}$ or $SF_{P,o} = (1 + 5 \times 1)^{0.59} = 2.88$
Non flooded pre-season < 180 days (indicating single cropping)	1.70	$SF_{BL,o}$ or $SF_{P,o} = (1 + 5 \times 0.29)^{0.59} = 1.70$

Source: calculated using equation (10) above with default values from IPCC 2006, volume 4, chapter 5.5, Table 5.14.

⁵ For a single crop, where the rice straw is usually ploughed back to the soil after the harvest of the crop and left for long period of time (i.e. rice straw is incorporated for a duration of > 30 days before cultivation), the straw is already mineralized being left in the dry field. Therefore the readily fermentable C component of the rice straw is less at flooding. This gives rise to lesser methane production when the soil is flooded for cultivation, therefore, 0.29 is used.

The above table is for rice straw only. To include other organic amendments following IPCC 2006 Table 5.14, the data will be:

- For compost, the $SF_{BL,o}$ or $SF_{P,o}$ will be $(1 + C \times 0.05)^{0.59}$;
- For farmyard manure, the $SF_{BL,o}$ or $SF_{P,o}$ will be $(1 + YM \times 0.14)^{0.59}$;
- For green manure, the $SF_{BL,o}$ or $SF_{P,o}$ will be $(1 + GM \times 0.50)^{0.59}$;
- C, YM, GM are application rate (tonne ha⁻¹) of compost, farmyard manure, and green manure, respectively.

The calculation of specific emission factor for the baseline (EF_{BL}) and for the project activity (EF_P) (kgCH₄/ha/day) is summarized in the table below.

Table 6: Specific emission factors for baseline, project and emission reductions (kgCH₄/ha/day) or (kgCH₄/ha/season)

		Baseline				Project Scenarios	Project				Emission Reduction Factor (EF_{ER})
		$SF_{BL,w}$	$SF_{BL,p}$	$SF_{BL,o}$	Emission Factor (EF_{BL})		$SF_{P,w}$	$SF_{P,p}$	$SF_{P,o}$	Emission Factor (EF_P)	
For regions/countries where double cropping is practiced	$EF_{BL,c}$	1.00	1.00	2.88	$EF_{BL,c}$ x 2.88	Scenario 1: change the water regime from continuously to intermittent flooded conditions (single aeration)	0.60	1.00	2.88	$EF_{BL,c}$ x 1.73	$EF_{BL,c}$ x 1.15
						Scenario 2: change the water regime from continuously to intermittent flooded conditions (multiple aeration)	0.52	1.00	2.88	$EF_{BL,c}$ x 1.50	$EF_{BL,c}$ x 1.38
For regions/countries where single cropping is practiced	$EF_{BL,c}$	1.00	0.68	1.70	$EF_{BL,c}$ x 1.16	Scenario 1: change the water regime from continuously to intermittent flooded conditions (single aeration)	0.60	0.68	1.70	$EF_{BL,c}$ x 0.69	$EF_{BL,c}$ x 0.46
						Scenario 2: change the water regime from continuously to intermittent flooded conditions (multiple aeration)	0.52	0.68	1.70	$EF_{BL,c}$ x 0.60	$EF_{BL,c}$ x 0.55

Option 2: using global default values derived from IPCC tier 1 approach.

Emission reductions shall be calculated, as per the equation (6), using default values of adjusted daily emission factor EF_{ER} (kgCH₄/ha/day) given below in different project scenarios:⁶

- For regions/countries where double cropping is practiced:
 - Use 1.50 (kgCH₄/ha/day) for project activities that shift to intermittent flooding (single aeration);
 - Use 1.80 (kgCH₄/ha/day) for project activities that shift to intermittent flooding (multiple aeration);
- For regions/countries where single cropping is practiced:
 - Use 0.60 (kgCH₄/ha/day) for project activities that shift to intermittent flooding (single aeration);
 - Use 0.72 (kgCH₄/ha/day) for project activities that shift to intermittent flooding (multiple aeration).

⁶ Under this option, $EF_{BL,c} = 1.30$ (kgCH₄/ha/day) from IPCC 2006, volume 4, chapter 5.5, Table 5.11. is used in Table 6 to derive at EF_{ER} .

The default values above consider the rice straw on field as the only organic amendment inputs. Other organic amendments such as compost, farmyard manure and green manure, which have been used in the pre-project scenario, may continue to be applied at the same or a lower rate during the crediting period, but do not affect the emission reductions estimated using the default values.

9. Monitoring

9.1 Data and Parameters Available at Validation

Data / Parameter	$EF_{BL,s,g}$
Data unit	kgCH ₄ /ha per season
Description	Baseline emission factor.
Equations	2
Source of data	As per the instructions in the appendix (Guidelines for measuring methane emissions from rice fields) and IPCC 2006, volume 4, chapter 5.5.
Value applied	N/A
Justification of choice of data or description of measurement methods and procedures applied	
Purpose of Data	Calculation of baseline emissions.
Comments	Regular measurements as per closed chamber method guidance, seasonally integrated.

9.2 Data and Parameters Monitored

Data / Parameter:	$EF_{BL,s,g}$
Data unit:	kgCH ₄ /ha per season
Description:	Baseline emission factor.
Equations	2
Source of data:	IPCC 2006

Description of measurement methods and procedures to be applied:	As per the instructions in the appendix (Guidelines for measuring methane emissions from rice fields) and IPCC 2006, volume 4, chapter 5.5.
Frequency of monitoring/recording:	Seasonally
QA/QC procedures to be applied:	
Purpose of data:	Calculation of baseline emissions
Calculation method:	As per the instructions in the appendix (Guidelines for measuring methane emissions from rice fields) and IPCC 2006, volume 4, chapter 5.5.
Comments:	

Data / Parameter:	$EF_{P,s,g}$
Data unit:	kgCH ₄ /ha per season
Description:	Project emission factor.
Equations	4
Source of data:	IPCC 2006
Description of measurement methods and procedures to be applied:	As per the instructions in the appendix (Guidelines for measuring methane emissions from rice fields) and IPCC 2006, volume 4, chapter 5.5.
Frequency of monitoring/recording:	Seasonally. Monitoring frequency dependent on measuring approach. If a closed chamber method is used, regular measurements should be conducted, seasonally integrated.
QA/QC procedures to be applied:	
Purpose of data:	Calculation of project emissions
Calculation method:	As per the instructions in the appendix (Guidelines for measuring methane emissions from rice fields) and IPCC 2006, volume 4, chapter 5.5.
Comments:	

Data / Parameter:	$A_{s,g}$
Data unit:	hectares
Description:	Aggregated project area in a given season s
Equations	2 and 4
Source of data:	IPCC 2006
Description of measurement methods and procedures to be applied:	To be determined by collecting the project field sizes in a project database. The size of project fields shall be determined by GPS or satellite data. Should such technologies not be available, established field size measurement approaches shall be used provided that uncertainties are taken into account in a conservative manner.
Frequency of monitoring/recording:	Seasonally
QA/QC procedures to be applied:	
Purpose of data:	Calculation of project emissions
Calculation method:	As per the instructions in the appendix (Guidelines for measuring methane emissions from rice fields) and IPCC 2006, volume 4, chapter 5.5.
Comments:	

Data / Parameter:	A_y
Data unit:	hectares
Description:	Aggregated project area in year y
Equations	6
Source of data:	IPCC 2006
Description of measurement methods and procedures to be applied:	To be determined by collecting the project field sizes in a project database. The size of project fields shall be determined by GPS or satellite data. Should such technologies not be available, established field size measurement approaches shall be used provided that uncertainties are taken into account in a conservative manner.
Frequency of monitoring/recording:	Annually

QA/QC procedures to be applied:	
Purpose of data:	Calculation of project emissions
Calculation method:	
Comments:	This parameter is only required to monitor if approach mentioned under option 1 or option 2 is used. Only compliant farms are considered. See section 9.3.

Data / Parameter:	L_y
Data unit:	Days/years
Description:	Cultivation period of rice in year y
Equations	6
Source of data:	To be determined using cultivation logbooks / remote sensing
Description of measurement methods and procedures to be applied:	To be determined using cultivation logbooks. Remote sensing imagery can be used to provide additional evidence on the cultivation period, and is recommended to provide additional transparency of the project.
Frequency of monitoring/recording:	Annually
QA/QC procedures to be applied:	
Purpose of data:	Calculation of project emissions
Calculation method:	
Comments:	This parameter is only required to monitor if approach mentioned under option 1 or option 2 is used. Only compliant farms are considered. Also, this parameter is not monitored when seasonal emission factor is applied.

9.3 Description of the Monitoring Plan

In order to determine whether the project fields are cultivated according to the project cultivation practice as defined by the project activity, and thus assure that measurements on the reference fields are representative for the emissions from the project fields, a cultivation logbook shall be maintained for all project fields. With the help of the logbook, all parameters that are part of the project cultivation practice, and at least the following, shall be documented by the farmers:

- a) Sowing (date);
- b) Fertilizer, organic amendments, and crop protection application (date and amount);
- c) Water regime on the field (e.g. “dry/moist/flooded”) and dates where the water regime is changed from one status to another;
- d) Yield.

Where possible, remote sensing can be used to collect and document relevant parameters that are part of the project cultivation practice.

In addition, farmers shall state whether they have followed fertilization recommendations provided with the introduction of the adjusted water management practice.

Project proponents shall assure that the project reference fields are cultivated in a way that they represent the ranges of cultivation practice elements on the project fields in a conservative manner with respect to methane emissions. Should farmers relevantly deviate from the defined project cultivation practice, so that their fields cannot be deemed to be represented by the reference fields any more, those fields shall not be taken into account for the determination of the aggregated project area $A_{s,g}$ of that season. This requirement shall assure that only those farms are considered for the calculation of emission reductions which comply with the project cultivation practice.

Reporting and verification shall be done on the basis of samples of the log-books from the farmers, according to the latest version of the “Standard for sampling and surveys for CDM project activities and programme of activities”.

Project proponents shall set up a database which holds data and information that allow an unambiguous identification of participating rice farms, including name and address of the rice farmer, size of the field and, if applicable, additional farm specific information as defined above.

10. References

1. 2006 IPCC Guidelines for National Greenhouse Gas Inventories
2. AMS-III.AU, “Methane emission reduction by adjusted water management practice in rice cultivation”
3. CDM General guidelines for SSC CDM methodologies, “Guidelines on the demonstration of additionality of small-scale project activities” and “General guidance on leakage in biomass project activities
4. CDM Tool for the Demonstration and Assessment of Additionality
5. Saving water with alternative wetting drying (AWD). [http://www.knowledgebank.irri.org/training/factsheets/water-management/saving-water-alternate-wetting-drying-awd#:~:text=Alternate%20Wetting%20and%20Drying%20\(AWD,disappearance%20of%20the%20ponded%20water](http://www.knowledgebank.irri.org/training/factsheets/water-management/saving-water-alternate-wetting-drying-awd#:~:text=Alternate%20Wetting%20and%20Drying%20(AWD,disappearance%20of%20the%20ponded%20water).

Appendix 1: Guidelines for measuring methane emissions from rice fields

Remote sensing

Project Proponents are permitted to utilise emerging technology (e.g. remote sensing) with known uncertainty to measure methane emissions. If this approach is taken, methane emissions must be measured both in the baseline and project scenario for the length of the project period using this method. These emerging technology approaches must be supported by peer-reviewed literature which validates their accuracy and uncertainty. Justification for the chosen approach should be documented in the Project Description Document supplemented with appropriate evidence. Any uncertainty in the approach used must be discounted for.

On the field measurements

The implementation of methane measurement in rice fields requires the involvement of experts in this field or at least experienced staff trained by experts (i.e. from research institutions). These guidelines cannot replace expertise in setting up chamber measurements. They rather set minimum requirements that serve for standardizing the conditions under which methane emissions are measured for projects under this methodology.

Project proponents shall prepare a detailed plan for the seasonal methane measurements before the start of the season. The plan shall include the schedule for the field and laboratory measurements, the logistics that are necessary to get the gas samples to the laboratory and a cropping calendar. The plan shall also include all reference field specific information regarding location and climate, soil, water management, plant characteristics, fertilizer treatment and organic amendments.

The following guidance is structured according to the steps from field measurement to emission factor calculation. Project proponents shall make sure that the measurements on project and baseline reference fields are carried out in an equal manner and simultaneously.

Table 1: On the field - technical options for the chamber design

Feature	Conditions	
Chamber material	<p>Option 1: Non-transparent</p> <ul style="list-style-type: none"> • Commercially available PVC containers or manufactured chambers (e.g. using galvanized iron); • Painted white or covered with reflective material (to prevent increasing inside temperature); 	<p>Option 2: Transparent</p> <ul style="list-style-type: none"> • Manufactured chambers using acrylic glass; • Advantage of transparent chambers: could be placed for longer time spans on the field if equipped with a lid that remains open between measurements and is only closed during measurements

	<ul style="list-style-type: none"> Only suitable for short-term exposure (typically 30 min) followed by immediate removal from the field 	
Placement in soil	<p>Option 1: Fixed base</p> <ul style="list-style-type: none"> Base made of non-corrosive material and remains in the field for the whole season; Base should allow tight sealing of the chamber; Base should have bores in the submerged section to allow water exchange between inside and outside; Base should be installed at least 24 hours before the first sampling 	<p>Option 2: Without base</p> <ul style="list-style-type: none"> Chamber have to be placed on the soil with open lid to allow escape of eventual ebullition
Auxiliaries of chamber	<ul style="list-style-type: none"> Thermometer for measuring the temperature inside the chamber; Fan (battery operated) inside the chamber for mix the inside air during sampling; Sampling port (rubber stopper placed in a bore of the chamber) 	
Basal area	Rectangular or rounded, but has to cover minimum of four rice hills (ca. 0.1 m ² minimum)	
Height	<p>Option 1: Fixed height</p> <ul style="list-style-type: none"> Total height (protruding base + chamber) should exceed plant height 	<p>Option 2: Flexible height</p> <ul style="list-style-type: none"> Adjustable to plant height; Chambers with different heights or modular design

Table 2: On the field – air sampling

Feature	Conditions
Replicate chambers per plot	Minimum requirement: Three replicate chambers per plo
Number of air samples per exposure / data points per measurement	Minimum requirement: Three samples per exposure
Exposure time	30 minutes
Daytime of measurement	Morning
Measurement interval	Minimum requirement: once per week
Syringe	Suitability test (leak proof) before measurement Preferably equipped with a lock for ease of handling
Sample storage until analysis	<ul style="list-style-type: none"> Storage < 24 h: air samples can remain in syringe; Storage > 24 h: transfer air samples into evacuated vial, store with slight overpressure

Table 3: Laboratory analysis

Feature	Conditions
Method	Gas Chromatograph with flame ionization detector (FID)
Injection	Direct injection or with multi-port valve and sample loop
Column	Packed (e.g. molecular sieve) or capillary column
Calibration	With certified standard gas each day of analysis before and after the analyses are done

Calculation of the emission rate for a plot (reference field)

1. For each gas analysis, calculate the mass of CH₄ emissions with the help of the following formula:

$$m_{CH_4,t} = c_{CH_4,t} \times V_{Chamber} \times M_{CH_4} \times \frac{1_{atm}}{R \times T_t \times 1000} \quad (\text{Equation 11})$$

Where:

- $m_{CH_4,t}$ = Mass of CH₄ in chamber at time t; mg
- t = Point of time of sample (e.g. 0, 15, 30 in case of three samples within 30 minutes)
- $c_{CH_4,t}$ = CH₄ concentration in chamber at time t, from gas analysis; ppm
- $V_{Chamber}$ = Chamber volume; L
- M_{CH_4} = Molar mass of CH₄; 16 g/mol
- 1_{atm} = Assume constant pressure of 1atm, unless pressure measurement is installed
- R = Universal gas constant; 0,08206 L atm K⁻¹ mol⁻¹
- T_t = Temperature at time t; K

2. Determine the slope of the line of best fit for the values of over time with the help of software (e.g. Excel):

$$s = \frac{\Delta m_{CH_4}}{\Delta t} \quad (\text{Equation 12})$$

Where:

- s = Slope of line of best fit; mg/min

3. Calculate the emission rate per hour for one chamber measurement:

$$RE_{ch} = s \times 60min / A_{Chamber} \quad (\text{Equation 13})$$

Where:

RE_{ch} = Emission rate of chamber ch ; $\text{mg/h} \times \text{m}^2$

ch = Index for replicate chamber on a plot

$A_{chamber}$ = Chamber area; m^2

4. Calculate the average emission rate of a chamber measurement per plot:

$$RE_{plot} = \frac{\sum_{ch=1}^{Ch} RE_{ch}}{Ch} \quad (\text{Equation 14})$$

Where:

RE_{plot} = Average emission rate of a plot; $\text{mg/h} \times \text{m}^2$

Ch = Number of replicate chambers per plot

Further procedure: from the average emission rates per plot of each chamber measurement, derive the seasonally integrated emission factor by integration of the measurement results over the season length. The simplest way of integration is multiplying the emission rate with the number of hours of the measurement interval (e.g. one week) and accumulating the results of every measurement interval over the season. Convert from mg/m^2 to kg/ha by multiplying with 0.01.